Visual Growth - An Integrated Suite of Reliability Growth Programs

68th MORS Symposium


Presenter: William J.

Broemen
2000


U.S. Army Materiel Systems Analysis Activity Aberdeen Proving Ground, Maryland

Backgroun d


- Reliability Growth: the improvement in a reliability parameter over a period of time due to changes in the product design or manufacturing process.
- AMSAA reliability growth model is probabilistic/management tool for:
 - Planning: Optimize testing and resources. Provide strategy to reduce risk.
 - Tracking: Ensure requirements are met in Reliability Demonstration Test.
 - Projection: Assess reliability at future milestones based on planned and implemented fixes to surfaced failure modes.



Planning Model used to quantify potential risk elements.



Tracking Model used to estimate current demonstrated relia



Projection Model used to estimate reliability at future milest

List of Reliability Growth Programs


- 1 Planning System Level Continuous
- 2 Planning Subsystem Level Continuous
- 3 Tracking System Level Continuous
- 4 Tracking System Level Discrete
- 5 Tracking Subsystem Level Continuous
- 6 Projection System Level Continuous Delayed Fixes
- 7 Projection System Level Continuous Instantaneous or Delayed Fixes
- 8 Projection System Level Discrete

Taxonomy of Reliability Growth Models

Level Phase	<u>System</u>	Subsystem		
Planning	anning Continuous			
Tracking	Continuous * Discrete *	Continuous		
Projection	Cont. Delayed Fixes * Cont. Instant/Delayed Fixed Fixe	xes *		

^{*} member of the Visual Growth suite

Structure of Visual Growth



Common Framework Across All Reliability Growth Programs

Splash Screen

U.S. Army Materiel Systems Analysis Activity
Acquisition and Technology Support Division
Reliability Methodology Team

Visual Growth

Beta Version 1.3






E<u>×</u>it

<u>N</u>ext>

This product has been developed at government expense. Redistribution of this software, without AMSAA's consent, is not authorized.

Main menu



Greetings


AMSAA Reliability Grov (V 1 a : 6 t) I (Vel - Continuous (1) [Greetings]					
<u>F</u> ile <u>H</u> elp					
This is the AMSAA Reliability Growth Tracking Model - Continuous Version					
This program tracks the improvement (growth) in reliability of a system during development for which usage is measured on a continuous scale, for example, time in hours or distance in miles.					
This program is designed for tracking the reliability of a system within a developmental test program by evaluating the reliability growth that results from the incorporation of design and quality fixes into the system during the test program. A design fix, also referred to as a design change or configuration change, is brought about by implementing corrective actions.					
< <u>B</u> ack <u>N</u> ext➤					

U.S. Army Materiel Systems Analysis Activity


Options description

AMSAA Reliabyit) G (Vt) // Arking Model - Continuous (2) [Options]						
<u>F</u> ile	<u>H</u> elp					
	There are 4 time-terminated options for this program:					
	(1) individual failure time data (3) mixed data (2) grouped data (4) gapped data					
	If the failure occurrence times are known, then use the option for "individual failure time data" (1).					
	If the system is tested on a configuration basis, then use the "grouped data" option (2).					
	If the development test program involves a combination of individual failure time data and grouped data, then use the "mixed data" option (3).					
	If there are gaps in the data (e.g., missing or nonrepresentative data), then use the "gapped data" option (4).					
	< <u>B</u> ack <u>N</u> ext>					

Options selection



Input




U.S. Army Materiel Systems Analysis Activity

Input window w/ Open

Open dialogue	box			? X
Look jn: My_Program	ns	<u> </u>		
string_search	acpm_exa	mple_data.txt	Crow_proi_e	xampli
test_cases	acpm_exa acpm_exa acpm_lfh.ti acpm_tm_i acpm_lfh_ti ampm_lfh_	mple_ptimes.txt	183example.t	xt OW
text_change	acpm_lfh.ti	xt	ift400.txt	file
Three_forms	acpm_tm_		iftdata.txt	
timer_example	ampm_lfh_		iftdata×3.txt	
Totals	,00000		arrys_data.tv	(t
acpm_decay.txt acpm_decay.txt	ampm_tm_	data.txt	plotcode.txt	
111			J	
File <u>n</u> ame: iftdata.txt			<u>0</u> pen	
Files of type: Text Files (*.txt	1		Cance	.
☐ Open as <u>r</u> ea	id-only			
Enter the total test time, T Enter the number of failures, N				ures, N
300		•]		ŀ
(greater than 0)		2	27	500
(greater thair o)				
			_, _	
Get Failure		≺ <u>B</u> ack	: C <u>l</u> ea	ar Input
Times				


U.S. Army Materiel Systems Analysis Activity

Input



U.S. Army Materiel Systems Analysis Activity

Model



U.S. Army Materiel Systems Analysis Activity

Goodness-of-Fit

AMSAA Reliability G. ove's Linicking Model - Continuous (6) [Output] AMSAA Reliability Growth Tracking Model - Continuous Individual Failure Time Data Goodness of Fit Results Total number of failures 27 Cramer-von Mises statistic .091 Table of Critical Values for Cramer-von Mises Goodness of Fit Test Number of Level of Significance Failures .20 .15 .10 .05 .01 20 .128 .146 .172 .217 .330 30 .128 .330 .146 .172 .218 If Cramer-von Mises statistic is greater than critical value at desired level of significance, then REJECT model. Print Form < Back Next >

Table of

AMSAA Reliability Growth Tricking Sodel - Continuous (7) [Output]

AMSAA Reliability Growth Tracking Model - Continuous Individual Failure Time Data


Table of Lower Confidence Bounds (LCBs) for the True MTBF at end of Reliability Growth Test								
Confidence Level (Percent) LCB			Confidence Level (Percent) LCB					
50	15.14		80	12.11				
55	14.63		85	11.52				
60	14.14		90	10.82				
65	13.66		95	9.87				
70	13.16		98	8.91				
75	12.65		99	8.34				

Print Form


< Back

See Plots >

Reliability growth




Failure rate



U.S. Army Materiel Systems Analysis Activity

Plot of



U.S. Army Materiel Systems Analysis Activity